


## Features

- FloorScore certified
- Patented Välinge® 5G Joint is strongest on the market, and proven to effectively reduce the chances of gapping
- Painted bevels add to a more realistic appearance. Made to closely resemble grout line on tiles
- · Built-in antimicrobial cork underlayment has superior sound absorption and thermal insulation properties
- Wear layer is enhanced with Armor Care technology, making it exceptionally stain and scratch resistant



Armor Care anti-stain and stratch resistant coating

Ultra-thick 0.5mm (20mil) wear layer Beautiful looks with rich texture

High desity composite core, waterproof Cork underlayment - antimicrobial and protects against mould and mildrew

Valinge® 5G locking system





<b>Product Information</b>				
Product Line	SureWood Luxury Vinyl Flooring			
Construction	WPC (wood polymer composite) vinyl			
Dimension	King size: 8mm (T) x 225mm (W) x 1510mm (L)			
Underlayment	1.5mm antimicrobial cork underlayment			
Wear Layer Thickness	0.5mm (20 mil)			
Finish	2-pass UV cured Urethane Finish			
Installation	Floating installation by clicking the end joints together. Please refer to Installation Instruction			
Warranty	Lifetime Residential and 12 Year Commercial Warranty			

Testing		
Classification	Method	Result
Class	ASTM F1700	Class III, Type B - Embossed
Slip Resistance	ASTM C1028-07	Dry: 0.80; Wet: 0.71
Static Load	ASTM F970	Applied Load: 1000 psi, Residual Indentation: 0.04mm
Impact Isolation Class	ASTM E492-09	72
Sound Transmission Class	ASTM E90-09	71
Dimensional Stability	ASTM F2199	Pass: ≤0.02 in. per linear foot
Resistant to Chemicals	ASTM F925	Pass: Not affected
Abrasion	ASTM D4060	Test Revolutions: 1000, 0.004% mass loss
Antibacterial Activity	ASTM G21-15	Pass: No growth observed on specimens
Reaction to Fire	EN13501-1	Class B fl-s1
Critical Radiant Flux	ASTM E648	Pass, >0.45 watts/cm <sup>2</sup>
Concentration of Dibutyl Phthalate	ISO 16000	<1 μg/m³ after 28 days
Concentration of Diethylhexyl Phthalate	ISO 16000	<1 μg/m³ after 28 days
Flexibility	EN435	No Damage



Packaging Information								
	Length	Width	Thickness	Sq. ft.	Weight			
	(mm)	(mm)	(mm)	per Carton	(lb. per carton)			
King Size	1510	225	8					
King Size Carton	1530	235	58	22.2	36			

Pallet Information								
	Length	Width	Height	Volume	# of carton	Sq. ft.	Weight	
	(mm)	(mm)	(mm)	(m³)	per Pallet	/pallet	(lb.)	
King Size Pallet	1530	940	970	1.40	60	1332	2160	